

BERNER ARCHITECTURAL RECESSED 12 & 16

AIR CURTAIN SERIES #ARD12 / ARC16

Mounts flush with the ceiling with built-in Intelliswitch[™] digital controller.



All heat

options



Berner AIR™ Add the Smart controller & app, includes BACnet & weather-based adaptive setting



800-245-4455 www.Berner.com

When the doors are open[™] BERNER AIR CURTAINS



Chosen by designers who are concerned with both aesthetics and protecting the intent of the space when the door is open.

Used at entrances to enhance or replace a vestibule to save energy and maintain comfortable interiors.

ARD12 - AMCA Certified and meets Building Code:

ASHRAE 90.1-2019, ASHRAE 189.1, and IECC-2015, allow AMCA Certified Air Curtains as an exception to a vestibule.

Custom Colors & Stainless Steel Available Requires a minimum of 15" clearance above the ceiling AIR CURTAIN Series #ARD12 / #ARC16 IDEAL APPLICATIONS: Main Entrances HEAT OPTIONS: Electric Steam Hot Water

ARD12 - For mounting heights up to 12' (environmental separation) and 10' (insect control) ARC16 - For mounting heights up to 16' (environmental separation) and 14' (insect control)

Lobbies

Standard Construction

• 15" high x 26" deep

- ARD12 1/2 hp motor(s) ten speeds
- · ARC16 1 hp motor(s) two speeds
- Factory installed Intelliswitch™ digital controller
- White aluminum exterior panel
- Top mounting only
- High efficiency, low noise Pro-V Nozzle
- Parts Warranty: Ambient - Five years Heated - Two years







Installation & Mounting

Simple to install, operate & maintain

- Single lengths up to 12'
- No Assembly Required
- 5/16" threaded inserts for top mounting
- Hinged bottom panel for easy access to internal components

Control Options

Factory installed Intelliswitch[™] digital controller:

- LED clock display
- Low voltage circuit for unit activation (BMS)
- External thermostat provision
- · Comfort Plus provision
- RoHS compliant
- · Temperature Probe (heated units only)

Sold Separately:

- Berner AIR[™] Smart controller & app, includes BACnet & weather-based adaptive setting
- Activation device: magnetic door switch



