


Vestibule Exception Compliance: up to 10 ft. AFF / Optimal Environmental Separation: up to 8 ft. AFF



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (hot water heated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

2 Year Limited Warranty



indoor use



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Coil Output (MBH)	Entering / Leaving Water Temp. (°F)	Water Flow (GPM)	Fluid Pressure Drop (FT. WG.)	Air Temp. Rise (°F)	Net Wt. (lbs)
AC08-F-1036W	36.00	2,054	1,545	869	84%	0.19	1 @ 1/5	27.1	180° / 166°	4.0	1.3	29°	63
AC08-F-1042W	42.00	1,985	1,547	1,015	82%	0.20	1 @ 1/5	32.9	180° / 166°	5.0	2.1	30°	71
AC08-F-1048W	48.00	2,013	1,585	1,189	80%	0.23	1 @ 1/5	37.9	180° / 164°	5.0	2.1	29°	78
AC08-F-1060W	59.00	2,040	1,552	1,431	80%	0.26	1 @ 1/5	46.0	180° / 161°	5.0	2.2	29°	94
AC08-F-1072W	72.00	1,928	1,394	1,568	83%	0.28	1 @ 1/5	55.8	180° / 164°	7.0	4.4	32°	112
AC08-F-2078W	78.00	2,054	1,546	1,884	82%	0.39	2 @ 1/5	62.8	180° / 162°	7.0	4.5	30°	114
AC08-F-2084W	84.00	1,985	1,547	2,030	82%	0.41	2 @ 1/5	67.3	180° / 160°	7.0	4.6	30°	139
AC08-F-2096W	96.00	2,013	1,585	2,378	80%	0.46	2 @ 1/5	80.4	180° / 162°	9.0	7.8	31°	154
AC08-F-2108W	108.00	2,040	1,553	2,620	80%	0.49	2 @ 1/5	88.6	180° / 160°	9.0	8.0	31°	170
AC08-F-2120W	118.00	2,040	1,552	2,862	80%	0.53	2 @ 1/5	97.8	180° / 160°	10.0	10.1	31°	185

See sheet EP-266E-AC & EP-266E-EC for amp draws/total load requirements.
600/3/60 power supply includes transformer housing, See drawing AC08-F-WTR-600

NOTES:

- Standard connection top, same end supply/return.
- Coil should be field supplied with a solenoid valve that energizes only when air curtain is energized. Consideration must be taken for freeze protection when necessary.
- Coil performance based on 65°F entering air temperature.
- Maximum leaving air temperature shall not exceed 120F.
- Consult factory for alternate entering air & water temperatures or GPM's.
- Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance; no reduction for optional EC motors.

MODEL NUMBER CONFIGURATION

AC08-F-1 036 W A-AC-CB-D-R-SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Berner AIR	Opt. Data Link	Opt. Display	Opt. Cabinet Finish
AC08	F	1, 2	036" - 120"	W=Hot Water Heated	AC & EC motors A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 230/1/50 A-XI = 600/3/60 † W = 277/1/60	AC (Std.) EC (Opt.)	CB=BASIC (Std.) CM=BMS (Opt.)	D=Physical Interconnect (daisy chain)	R=Remote Display TB=Tablet	SS=Stainless Steel CC=Custom Color

for Standard offering, leave options (Opt.) blank

STANDARD CONSTRUCTION

- 8 1/4" high x 20" deep
- 1/5 hp AC motor(s) - ten speeds
- Touchscreen interface with Intelliswitch™ digital controller, includes Berner AIR® BASIC (smart control)
- Clear satin anodized aluminum exterior
- Wall or Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Factory installed coil
- Filter (washable)

OPTIONS

- 1/5 hp EC motor(s) - ten speeds
- Berner AIR® BMS (smart control with BACnet and Modbus capabilities)
- Custom Color or Stainless
- Rear cover for top mounting to conceal fasteners

*Suitable for 50 Hz
† Add 5" to cabinet width for transformer

VELOCITY PROJECTION: Model AC08-F-1036W			
Distance from Nozzle (in)	40	80	120
Core Velocity (fpm)	859	588	547
Uniformity (%)	89%	87%	91%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Sound level measured 10' (3m) from the unit in free field:
1 motor: Min./Max. Speed: 50/55 dBA
2 motors: Min./Max. Speed: 53/58 dBA

Sound data is not AMCA certified.

Berner reserves the right to alter specifications without prior notice.



ARCHITECTURAL CONTOUR 8 - AC MOTORS

Hot Water Heated Air Curtain Electrical Performance Sheet

		120/1/60 (voltage code A) AC MOTOR AMP DRAW = 3.4 each		208/1/60 (voltage code B) AC MOTOR AMP DRAW = 1.7 each		240/1/60 (voltage code J) or 230/1/50 (voltage code V) AC MOTOR AMP DRAW = 1.7 each			
MODEL	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT
AC08-F-1036W AC08-F-1042W AC08-F-1048W AC08-F-1060W AC08-F-1072W	1	3.4	15	1	1.7	15	1	1.7	15
AC08-F-2078W AC08-F-2084W AC08-F-2096W AC08-F-2108W AC08-F-2120W	1	6.8	15	1	3.4	15	1	3.4	15

		277/1/60 (voltage code W) AC MOTOR AMP DRAW = 2.3 each		600/3/60 (voltage code A-XI) XFMR 600/120 0.5kVA per MTR @ 0.8 each AC MOTOR AMP DRAW = 3.4 each @ 120V		
MODEL	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT
AC08-F-1036W AC08-F-1042W AC08-F-1048W AC08-F-1060W AC08-F-1072W	1	2.3	15	1	0.8	15
AC08-F-2078W AC08-F-2084W AC08-F-2096W AC08-F-2108W AC08-F-2120W	1	4.6	15	1	1.6	15

Berner reserves the right to alter specifications without prior notice.

Berner.com Berner Air Curtains 800.245.4455
111 Progress Ave. / New Castle / PA / 16101 / USA

EP-266E-AC
July, 2025



ARCHITECTURAL CONTOUR 8 - EC MOTORS






Hot Water Heated Air Curtain Electrical Performance Sheet

		120/1/60 (voltage code A) EC MOTOR AMP DRAW = 4.4 each		208/1/60 (voltage code B) EC MOTOR AMP DRAW = 2.5 each		240/1/60 (voltage code J) or 230/1/50 (voltage code V) EC MOTOR AMP DRAW = 2.5 each			
MODEL	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT
AC08-F-1036W AC08-F-1042W AC08-F-1048W AC08-F-1060W AC08-F-1072W	1	4.4	15	1	2.5	15	1	2.5	15
AC08-F-2078W AC08-F-2084W AC08-F-2096W AC08-F-2108W AC08-F-2120W	1	8.8	15	1	5.0	15	1	5.0	15

		277/1/60 (voltage code W) EC MOTOR AMP DRAW = 2.2 each		600/3/60 (voltage code A-XI) XFMR 600/120 0.5kVA per MTR @ 0.8 each EC MOTOR AMP DRAW = 4.4 each @ 120V		
MODEL	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT	# CKTS	AMPS PER CIRCUIT	BREAKER RATING PER CIRCUIT
AC08-F-1036W AC08-F-1042W AC08-F-1048W AC08-F-1060W AC08-F-1072W	1	2.2	15	1	0.8	15
AC08-F-2078W AC08-F-2084W AC08-F-2096W AC08-F-2108W AC08-F-2120W	1	4.4	15	1	1.7	15

Berner reserves the right to alter specifications without prior notice.

AC08-F WATER HEATED SYSTEM: 120 - 277V



MODEL	NOZZLE WIDTH "A"	MOUNTING WIDTH "B"	UNIT WIDTH "C"
AC08-F-1036W	36.00 [914]	36.75 [934]	38.00 [965]
AC08-F-1042W	42.00 [1067]	42.75 [1086]	44.00 [1118]
AC08-F-1048W	48.00 [1219]	48.75 [1238]	50.00 [1270]
AC08-F-1060W	59.00 [1499]	59.75 [1518]	61.00 [1549]
AC08-F-1072W	72.00 [1829]	72.75 [1848]	74.00 [1880]
AC08-F-1078W	78.00 [1981]	78.75 [2000]	80.00 [2032]
AC08-F-2084W	84.00 [2134]	84.75 [2153]	86.00 [2184]
AC08-F-2096W	96.00 [2438]	96.75 [2458]	98.00 [2489]
AC08-F-2108W	108.00 [2743]	108.75 [2762]	110.00 [2794]
AC08-F-2120W	118.00 [2997]	118.75 [3016]	120.00 [3048]






NOTES:

- 1 AIR CURTAIN MUST BE INSTALLED SO AIR STREAM IS NOT OBSTRUCTED WHEN DEFLECTED 20° TO EITHER SIDE OF C.
- 2 ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
- 3 FIELD VERIFY DIMENSIONS.
- 4 ANCHORS TO SUPPORTING STRUCTURE BY OTHERS.
- 5 ADEQUACY OF SUPPORTING STRUCTURE IS TO BE VERIFIED BY A PROFESSIONAL STRUCTURAL ENGINEER.
- 6 THE LAST CHARACTER IN THE MODEL NUMBER - "W" DESIGNATES WATER HEATED UNIT.
- 7 DIMENSIONS IN INCHES [MILLIMETERS].
- 8 COIL CONNECTIONS LH STANDARD (AS SHOWN), OPTIONAL RH.

SHEET 1 OF 1

PROJECT	REV	0
LOCATION		
ARCHITECT		
ENGINEER		
DWG. NO.	AC08-F-WTR-120	TITLE: BERNER MODEL AC08-F AIR CURTAIN 120 - 277V WATER HEATED SYSTEM
DATE	21JAN2025	
BY	S. Beil	
REPLACES	28FEB2023	
BY	D. Johnson	BERNER INTERNATIONAL CORP. NEW CASTLE, PA.

AC08-F WATER HEATED SYSTEM: 600V



MODEL	NOZZLE WIDTH "A"	MOUNTING WIDTH "B"	UNIT WIDTH "C"
AC08-F-1036W	36.00 [914]	36.75 [934]	38.00 [965]
AC08-F-1042W	42.00 [1067]	42.75 [1086]	44.00 [1118]
AC08-F-1048W	48.00 [1219]	48.75 [1238]	50.00 [1270]
AC08-F-1060W	59.00 [1499]	59.75 [1518]	61.00 [1549]
AC08-F-1072W	72.00 [1829]	72.75 [1848]	74.00 [1880]
AC08-F-1078W	78.00 [1981]	78.75 [2000]	80.00 [2032]
AC08-F-2084W	84.00 [2134]	84.75 [2153]	86.00 [2184]
AC08-F-2096W	96.00 [2438]	96.75 [2458]	98.00 [2489]
AC08-F-2108W	108.00 [2743]	108.75 [2762]	110.00 [2794]
AC08-F-2120W	118.00 [2997]	118.75 [3016]	120.00 [3048]

NOTES:

- 1 AIR CURTAIN MUST BE INSTALLED SO AIR STREAM IS NOT OBSTRUCTED WHEN DEFLECTED 20° TO EITHER SIDE OF C.
- 2 ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
- 3 FIELD VERIFY DIMENSIONS.
- 4 ANCHORS TO SUPPORTING STRUCTURE BY OTHERS.
- 5 ADEQUACY OF SUPPORTING STRUCTURE IS TO BE VERIFIED BY A PROFESSIONAL STRUCTURAL ENGINEER.
- 6 THE LAST CHARACTER IN THE MODEL NUMBER - "W" DESIGNATES WATER HEATED UNIT.
- 7 DIMENSIONS IN INCHES [MILLIMETERS].
- 8 COIL CONNECTIONS LH STANDARD (AS SHOWN), OPTIONAL RH.

SHEET 1 OF 1

PROJECT		REV	0
LOCATION			
ARCHITECT			
ENGINEER			
DWG. NO.	AC08-E-WTR-600	TITLE:	BERNER MODEL AC08-E AIR CURTAIN 600V WATER HEATED SYSTEM
DATE	28FEB2023		
BY	D. Johnson		
REPLACES	22FEB2022		
BY	S. Beil		BERNER INTERNATIONAL CORP. NEW CASTLE, PA.