When the doors are open, BERNER AIR CURTAINS®



INTRODUCING THE BERNER ARCHITECTURAL ELITE 8 & 10

AIR CURTAIN SERIES AE08 & AE10

Designed to disappear as one enters the space.


Quiet, technologically advanced, and beautifully designed.

Made in U.S.A.



800-245-4455 Berner.com

Saving energy and creating healthy, comfortable environments



Standard Construction

- Intelliswitch[™] digital controller, includes Berner AIR[®] BMS (smart control with BACnet & Modbus integration capabilities)
- Cabinet: Brushed stainless steel, grade 304 (Optional: Anodized aluminum or Custom Color)
- Bottom Panel: Clear satin anodized aluminum
 (Optional: Custom Color or Stainless)
- Wall or Top Mounting (Optional: rear cover for glass transoms)
- High efficiency, low noise articulating Pro-V Nozzle
- Filter (washable)
- Parts Warranty: Ambient - Five years; Heated - Two years

Architectural Elite 8:

- Single lengths up to 10'
- 1/5 hp EC motor(s)

Architectural Elite 10:

- Single lengths up to 12'
- 1/2 hp EC motor(s)



Vestibule Exception: ASHRAE 90.1-2019, ASHRAE 189.1, and IECC-2015, allow AMCA Certified Air Curtains as an exception to a vestibule.



THE ARCHITECTURAL ELITE 8 & 10

Air curtains as smart as they are beautiful.

The perfect solution when aesthetics matter. Designed for those who are looking for a seamless integration of beauty, function and performance.

Built on Berner's strong engineering foundation, these air curtains save energy and protect the interior when the door is open.

Controls

THE ALL NEW BERNER INTELLISWITCH[™]

Built-in digital controller with touchscreen display and the BERNER AIR® smart control & app

- Effortless & Flexible choose from pre-set modes, adjust the motor speed, create a schedule, adjust the time delay, and more.
- Space heater setting and thermostat probe (heated units only)
- Low voltage circuit for air curtain activation
- Follows best practices for cyber security protocols

BERNER AIR[®] BMS PACKAGE

for Building Management Systems

- Allows full integration of the air curtain with the Building Management System via:
 - o BACnet-IP and BACnet-MS/TP
 - o Modbus-TCP and Modbus-RTU
- On-site, secure wi-fi connection recommended
- Activation device: Magnetic reed door switch
- Optional: Remote mounted Intelliswitch touchscreen display

Installation & Mounting

Simple to install, operate & maintain

- No Assembly Required
- Wall mounting brackets included
- 1/4" threaded inserts for top mounting
- Bottom access panel for easy access to internal components

